GFS-400-KT GENT SOLAR STREET LIGHT KIT





The GFS-400-KT is designed to be mounted onto an existing pole and replace mains powered street lighting offering an environmentally friendly, offgrid solution where traditional lighting has failed or is too costly to repair.

It has the same hardware as the GFS-400 (without the pole) and offers a reliable, vandal resistant solution that can be installed anywhere requiring reliability and performance without the costs of grid connection or energy supply.

APPLICATIONS

- Streets
- Roadways
- Intersections
- Car Parks
- Industrial
- Commercial
- Parks
- Recreation







GFS-400-KT SOLAR STREET LIGHT KIT



SPECIFICATIONS

MODEL GFS-400-KT

OPERATING PROFILE / OPERATION MODES

Standard 60W - **All night operation** - Unit operates at 100% (11220lm) until dawn. Standard 75W - **100% for 6 hours** - Unit operates at (14025lm) then dims to 20W until dawn Standard 100W - **100% for 4 hours** - Unit operates at (18700lm) then dims to 20W until dawn **NOTE**: Configurable TIMER settings for ON / OFF / DIM are available upon request.

NOTE. Comigurable mile ser	ttings for UN / UFF / DIM are available upon request.
LED	
Туре	CREE XP-G LED
Watts (Light Output)	60W (standard) 75W (optional) 100W (optional)
Lumens	11,220lm 14,025lm 18,700lm
CCT (Colour Temperature)	4000K (standard) / 3000K (optional)
Optics	T3 (Standard) 135° x 85° T5 (Optional) 110° x 135°
BATTERY	
Autonomy	60 hours (5 nights)*
Battery Type / Capacity	2 x 12v 110Ah (2640Wh) Sealed GEL AGM Batteries
SOLAR PANEL	
Watts (p) / Type	454W Monocrystalline
Efficiency	21%
UNIT	
Package Dimensions	Crate: 1680 x 1640 x 570 mm / 66" x 64.6" x 22.4"
Package Weight	Crate: 270 KG / 595.2 lb
Product Weight	Complete Kit: 188 KG / 414.5 lb
Sail Area / EPA	1.1m2 / 11.84ft2
ENVIRONMENTAL	
Operating Temp. Range	-20°C to 60°C / -4°F to 140°F
IP Rating	IP65 construction with IP68 waterproof connectors
WARRANTY	
Warranty Period	5 years (Unit) / 25 years (Solar Panel)**
OPTIONS	
PROTECTION	Solar panel stone guard
	LED lens stone guard
	Anti-climbing spike collar
	Light spill shield front / back
	Goose neck outrigger extension
TWIN HEAD LED OPTION	Twin head 4K CCT / 180° / 90° configuration
	Twin head 3K CCT / 180° / 90° configuration
BATTERY BOX OPTIONS	Battery box, grey powder coated
	Battery box, stainless steel 316
	Vandal resistant battery box upgrade kit
	In-ground pit box with galvanised lock lid
IoT SMART CITY READY	Using optional GFS-SAM monitoring system

^{*}Based on fully charged battery at 30W / **full warranty information is available at >> greenfrog systems.com.au/warranty information is available at a system information information is available at a system information informat

GFS-400-KT SOLAR STREET LIGHT KIT





KIT CONTENTS INCLUDE:


- 1. Instruction Manual
- Serial Number Plate
- Wooden Packing Crate
- Solar Panel Assembly LED Light
- Light Arm
- Light Cable Extension

90 [3.5in]

- Bird Guard
- Batteries (x2)
- Solar Controller









A (1:3)



MOUNTING OPTIONS



PHOTOMETRICS



GFS-400-KT SOLAR STREET LIGHT KIT



LIGHT DISTRIBUTION

FRONT VIEW

